

GPON OLT 8PON

Product Overview:

GPON OLT 8PON is a small capacity and enhancement mode cassette GPON OLT, meeting the requirements of *ITU-T G.984/G.988* and relative standards of *China Telecom/Unicom GPON*, possessing super GPON access capacity, carrier-class reliability and the complete security function. It can satisfy long-distance optical fiber access requirement on account of its excellent management, maintenance and monitoring capability, abundant service features and flexible network mode. GPON OLT 8PON can be used with network management system so as to provide users with the perfect solution.

It provides 8*downlink GPON port, 4 *GE combo port,2*Alarm port and 2* 10G SFP+ port for uplink. The height is only 1U for easy installation and space saving. GPON OLT 8PON is suitable for Broadcast *three in one*, video surveillance network, enterprise LAN, Internet of Things, etc.



- 1U, 19 inch
- 1+1 power redundancy
- 8* fixed GPON port
- 4*GE COMBO , 2*10GE SFP+
- 1* console port

GPON OLT 8PON

Product Specification:

Item	GPON OLT 8PON
Service Port	8*PON port,4*GE COMBO port, 2*10GE SFP+ port
Redundancy Design	Dual power supply Support AC input, double DC input and AC+DC input
Power Supply	AC: input 100~240V 50/60Hz; DC: input 36V~75V;

GPON OLT 8pon Datasheet V1.0

Power Consumption	≤90W
Dimensions (Width x Height x Depth)	440mm×44mm×300mm
Weight (Full-Loaded)	≤6.5g
Environmental Requirements	Working temperature: -10°C~55°C Storage temperature: -40°C~70°C Relative humidity: 10%~90%, non-condensing

Product Features:

Item		GPON OLT 8PON
PON Features		ITU-TG.984.x standard Maximum 20 Km PON transmission distance access 128 terminals for single fiber PON Uplink and downlink triple churning encrypted function with 128Bits ONU terminal legitimacy certification, report illegal ONU registration DBA algorithm, the particle is 1Kbit/s Standard OMCI management function ONU batch software upgrade, fixed time upgrade, real time upgrade PON port optical power detection
L2 Features	MAC	MAC Black Hole Port MAC Limit 64K MAC (packet exchange chip cache 2MB, external cache 720 MB)
	VLAN	4K VLAN entries Port-based/MAC-based/protocol/IP subnet-based QinQ and flexible QinQ (StackedVLAN) VLAN Swap and VLAN Remark PVLAN to realize port isolation and saving public-vlan resources GVRP
	Spanning Tree	STP/RSTP/MSTP Remote loop detecting
	Port	Bi-directional bandwidth control Static link aggregation and LACP(Link Aggregation Control Protocol) Port mirroring
Security Features	User's Security	Anti-ARP-spoofing Anti-ARP-flooding IP Source Guard create IP+VLAN+MAC+Port binding Port Isolation MAC address binding to the port and MAC address filtering IEEE 802.1x and AAA/Radius authentication

GPON OLT 8pon Datasheet V1.0

	Device Security	<p>Anti-DOS attack(such as ARP, Synflood, Smurf, ICMP attack), ARP detection, worm and Msblaster worm attack</p> <p>SSHv2 Secure Shell</p> <p>SNMP v3 encrypted management</p> <p>Security IP login through Telnet</p> <p>Hierarchical management and password protection of users</p>
	Network Security	<p>User-based MAC and ARP traffic examination</p> <p>Restrict ARP traffic of each user and force-out user with abnormal ARP traffic</p> <p>Dynamic ARP table-based binding</p> <p>IP+VLAN+MAC+Port binding</p> <p>L2 to L7 ACL flow filtration mechanism on the 80 bytes of the head of user-defined packet</p> <p>Port-based broadcast/multicast suppression and auto-shutdown risk port</p> <p>URPF to prevent IP address counterfeit and attack</p> <p>DHCP Option82 and PPPoE+ upload user's physical location</p> <p>Plaintext authentication of OSPF, RIPv2 and BGPv4 packets and MD5</p> <p>cryptograph authentication</p>
Service Features	ACL	<p>Standard and extended ACL</p> <p>Time Range ACL</p> <p>Flow classification and flow definition based on source/destination MAC address, VLAN, 802.1p, ToS, DiffServ, source/destination IP(IPv4/IPv6) address, TCP/UDP port number, protocol type, etc</p> <p>packet filtration of L2~L7 deep to 80 bytes of IP packet head</p>
	QoS	<p>Rate-limit to packet sending/receiving speed of port or self-defined flow and provide general flow monitor and two-speed tri-color monitor of self-defined flow</p> <p>Priority remark to port or self-defined flow and provide 802.1P, DSCP priority and Remark</p> <p>CAR(Committed Access Rate), Traffic Shaping and flow statistics</p> <p>Packet mirror and redirection of interface and self-defined flow</p> <p>Super queue scheduler based on port or self-defined flow. Each port/</p> <p>flow supports 8 priority queues and scheduler of SP, WRR and SP+WRR.</p> <p>Congestion avoid mechanism, including Tail-Drop and WRED</p>
	IPv4	<p>ARP Proxy</p> <p>DHCP Relay</p> <p>DHCP Server</p> <p>Static Routing</p> <p>RIPv1/v2</p> <p>OSPFv2</p> <p>Equivalent Routing</p> <p>Routing Strategy</p>

GPON OLT 8pon Datasheet V1.0

	Multicast	<p>IGMPv1/v2/v3</p> <p>IGMPv1/v2/v3 Snooping</p> <p>IGMP Filter</p> <p>MVR and cross VLAN multicast copy</p> <p>IGMP Fast leave</p> <p>IGMP Proxy</p> <p>PIM-SM/PIM-DM/PIM-SSM</p> <p>PIM-SMv6, PIM-DMv6, PIM-SSMv6</p> <p>MLDv2/MLDv2 Snooping</p>
Reliability	Loop Protection	<p>EAPS and GERP (recover-time <50ms)</p> <p>Loopback-detection</p>
	Link Protection	<p>FlexLink (recover-time <50ms)</p> <p>RSTP/MSTP (recover-time <1s)</p> <p>LACP (recover-time <10ms)</p> <p>BFD</p>
	Device Protection	<p>VRRP host backup</p> <p>1+1 power hot backup</p>
Maintenance	Network Maintenance	<p>Port real-time, utilization and transmit/receive statistic based on Telnet</p> <p>RFC3176 sFlow analysis</p> <p>LLDP</p> <p>GPON OMCI</p> <p>RFC 3164 BSD syslog Protocol</p> <p>Ping and Traceroute</p>
	Device Management	<p>CLI, Console port, Telnet and WEB</p> <p>SNMPv1/v2/v3</p> <p>RMON (Remote Monitoring)1,2,3,9 groups MIB</p> <p>NTP</p> <p>network management</p>

Purchase Information:

Product name	Product description
GPON OLT 8PON	8*PON, 4*GE COMBO port,2*ALARM, 2*10GE SFP+, double AC/DC power supply
DC Power Supply	DC Power module for GPON OLT 8PON
AC Power Supply	AC Power module for GPON OLT 8PON